





Wall Lights | 2 x powerLED 4 W DC 630 mA | CRI 80
92619M12



Technical data	
Type	Surface
Installation position	Wall lights
Installation environment	Outdoor
Light Source	LED
Optics	Double Extra Wide Flood
Light emission direction	downward and upward
Nominal power	4 W DC
Source lumens	438 lm
Current intensity	630mA
CCT / Tone	2700 K
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP66
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DALI - 1-10V
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	1 m
Resin potting	Yes
Type of light emission	Double emission
Net weight	0.22 Kg
Electrostatic discharge protection	No
Surge protection	No
Product technological characteristics	Acquastop - Clearshield - TVS

Finishing casing

Material	Aluminium 6060
Colour	Embossed white RAL 9003
Processing	Open pore anodizing + Powder Coating

Finishing diffuser

Material	Silicone resin
Colour	transparent

Electronics

 89420
On/Off Driver 198-264V AC / 180-275V DC (1 art.)

 99179
On/Off Driver 198-264V AC (1 - 3 art.)

 99186
On/Off Driver 198-264V AC (1 - 6 art.)

 83102
DALI-2 Controller (1 - 7 art.)

Cables Electrification

Cable connector	No
-----------------	----



Wall Lights | 2 x powerLED 4 W DC 630 mA | CRI 80
92619M12

Double emission wall lights for outdoor application. The super warm LED light source with a double extra wide flood light distribution is composed of 2 powered LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 438 lm, with a 109.5 lm/W nominal luminous efficacy.

The device body is made of aluminium 6060 and features a embossed white ral 9003 finish, processed by means of open pore anodizing + powder coating; the diffuser is made of silicone resin. The ingress protection degree is IP66; the total weight is of 0.22 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 4 W. The power supply cable is included and features a 1 m length.

The device features protection class III and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features

Source lumens	438 lm
Colour temperature	2700 K
Standard Deviation of Colour Matching	1/16 ANSI BIN
Colour rendering index	80 Ra
Standard Operating Ambient Temperature	-20 / +50°C
Ordinary temperature on the glass	40°C

LED Life / Failure Ratio

L70 B10 C0 361980h (at Tj 60 Ta 25)